

WFLO-407-II

Oxygen Scavenger

Description

APPLICATION: CHEMFLO-407-II is a ready-to-use liquid oxygen scavenger which prevents internal boiler corrosion due to dissolved oxygen. Product reacts chemically with the dissolved oxygen to prevent pitting of boiler heating internals.

BENEFITS:

**PREVENTS THE PITTING OF BOILER INTERNALS.
REACTS WITH DISSOLVED OXYGEN INSTANTLY.
PRODUCT IS EASILY MONITORED WITH A QUICK TEST.**

PHYSICAL PROPERTIES:

Physical State	: Light liquid
Density	: 1.1.
pH of 1% Solution	: 6.5
Solubility	: Complete in water

FEEDING: For best results, CHEMFLO-407-II should be fed to the deaerator storage or feed water tank. Product is compatible with other boiler treatment products. Avoid excessive agitation when mixing.

DOSAGES: Dependent upon the temperature and dissolved oxygen content of the feed water. Average dosage is 2-4 ounces per 1000 gallons of make-up water.

TESTING & CONTROL: Treatment levels are monitored with the Test Kit.

HANDLING & STORAGE: Read label completely before use. See label for first aid instructions. Keep containers closed when not in use. Store containers in an area free of temperature extremes.

PACKAGING: Available in 20,35 and 50 plastic containers.